

UV-Integrator 14 X10



The UV-Integrator

The UV-Integrator 14 is a high quality UV measuring instrument. It is used to measure UV energy of different light sources, especially on printing machines. It is ideal to ensure quality control of printing and drying processes. Big size, heavy duty pass-through Integrator with a diameter of 140 mm. It is reliable and simple to use.

The UV-Integrator 14 is available in six different measuring ranges*:
(Please state upon order)

Item 8.11 UV-Integrator 14, Type 11, Diazo	350 – 460 nm
Item 8.21 UV-Integrator 14, Type 21, UV-A	315 – 400 nm
Item 8.31 UV-Integrator 14, Type 31, UV	250 – 410 nm
Item 8.41 UV-Integrator 14, Type 41, UV-B	280 – 315 nm
Item 8.51 UV-Integrator 14, Type 51, UV-C	230 – 280 nm
Item 8.61 UV-Integrator 14, Type 61, UV-V	395 – 445 nm


*further spectral ranges available upon request

By addition of the incidence of the light quantities during the exposure cycle, relative values are calculated. Because of uneven radiation distribution of the UV light source and different type of construction of the measuring devices by different manufacturers, different readings may appear under the same measurement conditions.

Technical Data:

Spectral range:	UV-C 230 – 280 nm
Measuring range:	0 to 500 mW/cm ²
Display:	6-digit LCD
Display range:	0 to 99,999 mJ/cm ²
Power source:	long life 3.6 V Lithium Battery
Power consumption:	100 μ A
Battery service life:	10,000 hrs
Dimensions:	\varnothing 5.5" (140 mm) height 1/2" (13 mm)
Weight:	approx. 17.5 ounce (500 grs.)
Temperature range:	0 to 45° C
Heat protection:	Heat shield on back plate
Base Accuracy:	\pm 5 %

In the standard version
it is measuring an integral
in the spectral range
from 230-280 nm,
with a peak
at the area of 265 nm.



While on the conveyer belt, the UV-Integrator 14 can withstand max. 110° C / 230° F for up to 10 seconds. The temperature of the housing should not exceed 45° C / 113° F.

Calibration:

In order to keep its full function and precision it is recommended to have re-calibration done once per year. Re-calibration will also be necessary after change of battery. Ongoing, PTB traceable calibration with certificate

Warranty: 2 years from the date of purchase, for the German quality battery we guarantee one year